



Specification FXE-L 400-50+			
Nominative Force: 15,2kN		lifting capacity EN 13155/WLL	
Materialthickness >15mm (100%)		WLL= 400kg	
2,1 kVA			
U: 380-480V Pulse		Protection Class IP 65	
R: 12,8Ω		Protectiv Earth SK I	
Max. Load capacity at sheets and 4-edge pipes			
T material thickness	Lmax (mm)	Wmax (mm)	Wll (kg)
>=4mm	1800	1000	70
>=6mm	2000	1000	140
>=8mm	2000	1000	200
>=10mm	2500	1000	250
>=15mm	3000	1000	400

Schutzvermerk nach DIN ISO 16016 beachten! Nachdruck nur mit unserer Genehmigung!			
All rights reserved according to DIN ISO 16016! Reprint with our permission only!			
02	Tabellenwerte	24.10.2023	TW
rev.	change	date	name

3,2 / -0,05 / -0,2 tolerance

ISO 7168 M

date name

drawn 13.01.2023 TW

edit 24.10.2023

appr. 24.10.2023 TW

**FLAIG**  
Magnetsysteme  
www.flraig-te.de

material:	weight: 23.00
drawing no.:	<b>0014517</b>
description:	<b>FXE-L 400-50+</b>
part no.:	<b>10600411</b>
scale: 1:3.5	Status: Freigegeben
sheet 1 / 1	A3