

Specification FXE 16000-100			
Nominative Force: 580 kN		lifting capacity EN 13155/WLL	
Materialthickness >35mm (100%)		WLL= 16000kg at air gap 0,6mm	
15,9 kVA			
U: 380-480V Pulse		Protection type IP 65	
R: 2x 1,7Ω + 4x 2,0Ω		Protection category SK I	
Max. Load capacity at sheets and 4-edge pipes			
T material thickness	Lmax (mm)	Wmax (mm)	Wll (kg)
>=10mm	3000	2000	4200
>=20mm	4500	2500	6400
>=35mm	6000	3200	16000

Schutzvermerk nach DIN ISO 16016 beachten! Nachdruck nur mit unserer Genehmigung!		tolerance		material:		weight: 800.00	
All rights reserved according to DIN ISO 16016! Reprint with our permission only!		3,2 / -0,05 / -0,2		ISO 7168 M		drawing no.: 0015783	
		date		name		description: FXE-HD 16000-100	
		drawn 13.01.2022		BW			
		edit 19.10.2023					
		appr. 19.10.2023		TW			
04 Tabellenwerte 19.10.2023 TW		 www.flaig-te.de		part no.: 106016003		sheet 1 / 2	
03 Gewicht 30.06.2023 TW						A3	
02 Überarbeitet 27.01.2023 TW							
rev. change date name				scale: 1:10		Status: Freigegeben	




RADIO REMOTE CONTROL:

Please note when using the remote control:
First press the red button for ON/OFF;
the Green Radio LED lights

- For switching aim for the magnet.
- Function and operation of each button see section 3 of this manual!
- Operate the magnet only by one person!
- Max. Reach 25m
- When the red Battery-LED lights change the battery

LIFTING SENSOR:

With integrated Lifting Sensor "Magnetize" and "Demagnetize" on floating Load and Lifting Magnet is not possible!



FRONT BOARD CONTROL PANEL:

The Lifting Magnet FXE is controlled via 4 built pushbuttons, they are from left to right:
PICK-UP with red LED • FULL-MAG with green LED • SAFE with orange LED • DE-MAG with white LED

Connect the lifting magnets at 400V mains voltage. The white LED above the button DE-MAG flashes to indicate that the magnet is in an undefined state.

Lifting in PICK-UP mode:

To check whether the workpiece can be transported with sufficient safety, or to lift a single sheet metal from a stack. Place the magnet on the workpiece and press the PICK-UP button, the orange Cycyle LED will flash briefly above the SAFE key. The red LED above the PICK-UP button then lights up to indicate that the magnet is activated with partial power. **In this state, the workpiece may only be lifted slightly but must not be transported under any circumstances!**

Transport in FULL-MAG operation:

After checking the safety by means of the PICK-UP operation or directly from the DE-MAG switching state, the maximum magnetization can be triggered with this key. After pressing, the orange cycle LED above the SAFE key lights up briefly and then the green status LED above the FULL-MAG key turns on to indicate that the maximum magnetization has occurred. Carry out transports only if the green LED lights up and the alarm LED (SAFE) does not flash!

Releasing the workpiece by DE-MAG:

To release the workpiece, the SAFE and DE-MAG keys must be pressed simultaneously. The orange cycle LED above the SAFE key lights up briefly and then the white status LED above the DE-MAG key lights up.

LED signal lights:

For better visualisazion a LED signal light is mounted on the magnet. The signal lights show the same status as the lights on the front board control panel.

Schutzvermerk nach DIN ISO 16016 beachten! Nachdruck nur mit unserer Genehmigung!					tolerance	material:	weight: 800.00	
All rights reserved according to DIN ISO 16016! Reprint with our permission only!					ISO 7168 M	drawing no.:	0015783	
				date	name	description: FXE-HD 16000-100		
				drawn	13.01.2022	BW		
				edit	19.10.2023			
				appr.	19.10.2023	TW		
04	Tabellenwerte	19.10.2023	TW	 www.flaig-te.de		part no.:	106016003	sheet
03	Gewicht	30.06.2023	TW				2 / 2	
02	Überarbeitet	27.01.2023	TW				A3	
rev.	change	date	name	scale: 1:10	Status: Freigegeben			