



Load capacity according to EN 13155/WLL
 Load capacity on flat material (from 10 mm material thickness): 150 kg
 Load capacity on 90° profile outside/top: 90 kg
 Load capacity on 90° profile inside/bottom: 75 kg

Workpiece temperature / contact time / load capacity:
 -At 250°C 100% put on time / 100% load capacity
 -At 300°C max. 50% put on time (contact time = cooling time, max. 4 minutes)
 85% load capacity
 -At 350°C max. 33% put on time (contact time = cooling time/2, max. 4 minutes)
 75% load capacity

Schutzvermerk nach DIN ISO 16016 beachten! Nachdruck nur mit unserer Genehmigung!			tolerance	material:	weight: 5.50	
All rights reserved according to DIN ISO 16016! Reprint with our permission only!			ISO 7168 M	drawing no.:	0018489	
			date	name	description: FX-VV 150 HOT	
			drawn 27.07.2022	TW		
			edit 18.12.2023			
			appr. 18.12.2023	TW		
			 www.flraig-te.de		part no.:	sheet 1 / 1
						11010155-1
03	Überarbeitet	18.12.2023	TW			
02	Bemaßung hinzu	20.11.2023	TW			
rev.	change	date	name	scale: 1:1.5	Status: Freigegeben	